

## **SRMix**

# The ultimate side-entry mixer Ultra Compact. Robust. Consistent Results.

#### **Benefits**

- · Static safety sealing
- Ideal for thin walls
- Designed for confined spaces

#### **Process Limits**

- Tanks: Up to 5,000 m<sup>3</sup>
- Density: 1.3
- Viscosity: 500 cp
- Pressure: From 0 to 5 bar
- Fluid temperature: From 0 to 100 °C

### **Main Applications**

- Raw material storing
- End product storing
- Homogenezing
- Biofuels, alcohol, additives preparing
- Water treatment
- Storage of oil (palm, sunflower)
- And many others



#### **Main Characteristics**

- Reliable gearbox transmission
- Wetteed parts in S.S. 304L
- Single mechanical seal

#### **Optional Features**

- ATEX compliance
- Wetted parts in S.S. 316L
- Flange ASME B16.5 150 lbs from 6" to 24"
- Others options available upon request

#### **3 Standard Models**







	SRGJ340	SRGJ410	SRGJ550
Rated power	0,75 kW	3 kW	5,5 kW
Weight	37 kg	70 kg	116 kg
Propeller diameter	340 mm	410 mm	550 mm
Shaft length	500 mm	550 mm	600 mm
Secondary sealing		Χ	Χ
Min. flange size	DN150 PN10		
Flange for propeller insertion	DN400	DN450	DN600



Flow Pathways

#### Milton Roy Mixing® is a trademark of Ingersoll Rand®.

Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is committed to helping make life better. We provide innovative and mission-critical industrial, energy, medical and specialty vehicle products and services across 40+ respected brands designed to excel in even the most complex and harsh conditions where downtime is especially costly. Our employees connect to customers for life by delivering proven expertise, productivity and efficiency improvements. For more information, visit www.IRCO.com.





